THIEL ENGINEERING CONSULTANTS

FALCON CAPITAL DOMESTIC WELL PUMPING TEST REPORT

FALCON CAPITAL DOMESTIC WELL PUMPING TEST REPORT

PREPAREED FOR:

FALCON CAPITAL, LLC.

PREPARED BY:

TEC 1, INC. 500 DAMONTE RANCH PARKWAY, SUITE 1056 RENO, NV 89521 (775) 352-7800 FAX: (775) 352-7929

MARCH, 2003

FALCON CAPITAL DOMESTIC WELL PUMPING TEST REPORT

Introduction

The Falcon Capital Domestic Well is located on the northwest side of Washoe Valley, Washoe County, Nevada. The location is in NW1/4, NE1/4, Section 23, Township 17 North, Range 19 East, Mount Diablo Baseline and Meridian. The attached Site Map shows this well location.

The Falcon Capital Well is an 8" diameter, 695' deep well. This well was drilled from January 8, 2003 to February 11, 2003 (see attached well log).

The purpose of performing a step drawdown pumping test (48-hour test) at the Falcon Capital Domestic Well was to determine the well capacity and its potential and provide data for the evaluation of the potential impact from future pumping.

Well Testing Procedures

• Static water lever (SWL) before test: 246.83 feet below the land surface.

• Pump set at 600 ft below the land surface for the testing.

Perls - 290-690

- Step-drawdown test run on February 24~26, 2003.
- Test consisted of two steps, with last step being pumped at a higher rate than the first step. Both steps lasted 24 hours.
- Average pumping rates approximately (totalizing meter malfunctioning): 200 gpm for the first step and 250 gpm for the second step.
- Water level at the pumping well was monitored at time intervals sufficient to monitor
 the water level changes; specific water level monitoring data is included in the
 Appendix.
- Water level at another well (Washoe County Old Washoe Well) southeast of the pumping well at a distance of approximately 980 ft was also monitored. The drawdown at end of the 48-hour test at this monitoring well is approximately 0.5 ft. It is not known whether the Washoe County well was pumped during the pumping test time period. However, during the first 4 hours of the pumping test, the Washoe County well was not pumped and the drawdown at the Washoe County well is 0.1 ft.
- Water Quality sampling at 4 hour after the test began.

Nover got W.Q.

• Test results (See attached test results and calculations)

Testing Results and Discussion

Step Drawdown Test

- Drawdown varied from approximately 46.17 feet at 200 gpm to 67.71 feet at the end
 of Step 2 at 250 gpm. The specific capacity ranged from approximately 4.33 to 3.69
 gallon per minute per foot of drawdown (gpm/ft).
- The specific capacity results show that specific capacity varies with the pumping rate. The higher the pumping rate, the lower the specific capacity. This is due to the fact that the well has a lower efficiency at a higher pumping rate.

Unsteady Drawdown Test (Early Portion of the First Step and Recovery)

- The drawdown vs. time curve attached indicates that the drawdown stabilized at approximate 1080 minutes at a pumping rate of approximately 200 gpm.
- Aquifer parameters estimated from the unsteady test and the recovery data based on the Theis solution are as follows:

Parameter	Pumping	Recovery		
Transmissivity (T: ft2/day)	1252	26422		
Storage Coefficient (S)	0.00021	2.7791E-217		

^{*}The straight-line method (Jacob's) was used.


• The recovery data was influenced by the water in the pump pipe, therefore, the result is not as good as the data from the pumping portion.

Recommendations:

- Based on the testing results it is recommended that the sustainable pumping rate be 600 gpm with the pump set at 600 ft deep.
- No water quality recommendations can be made at this time. Water quality data will available in approximately 30 days. The water temperature is approximately 75° F.

Appendix:

- Location map
 Well Log
 Calculations
 Pumping Test Data Logs



STATE OF NEVADA DIVISION OF WATER RESOURCES WELL DRILLER'S REPORT

office use only Log No..... Permit No.....

Basin... NOTICE OF INTENT NO

1. OWNER

G.P.M.

100

250

Draw Down

80 230

420

(Feet Below Static)

Time (hours)

Falcon Capital LLC

ADDRESS AT WELL LOCATION

Joy Lake Road

MAILING ADDRESS 500 Damonte Rch Pkwy #1056

Reno NV 89521

2. Location PERMIT NO.	NW 1/4 N			Sec 23 T		R 19E Washoe County SUBDIVISION NAME
3. WORK I X New Well Deepen	PERFORME Replace Abandon	Recond Other	dition	X Domestic		OSED USE 5. W ELL TYPE Irrigation Test Cable X Rotary RVC Air Other X Mud
6.			GIC LC)G		8. WELL CONSTRUCTION
Material		Water Strata		To	Thick-	,
Clay & boulders.			0	95	ness 95	12 1/4 inches 0 feet 695 feet
Red clay.			95	111	16	1001
Black rock.			111	117	•	Size O.D. Weight/Ft. Wall Thickness From 7 (Inches) (Pounds) (Inches) (Feet) Feet
Volcanic.	((117	143	26	
Red clay.		-	143	160	17	Perforations::
Lost Circulation.			160	310	150	Type Perforation Factory Size perforation 3/32 x 3"
Black Rock.			310	360	50	ALICANA AND AND AND AND AND AND AND AND AND
Lost Circulation			360	437	77	From feet to feet
Volcanic & clay.			437	673	236	
Rock.			673	690	17	Depth of Seal 100 feet Neat Cement
Clay.			690	695	5	Solicite Great
		1 1			0	From 100 feet to 695 feet
					0 0 0	9 WATER LEVEL Static water leve270 feet below land surface Artesian flow 0 GPM 0 P.S.I.
				<u> </u>		Water Temperature 68 Degrees F Quality
Date started Date completed	1-8 -03 2-11 -03				,	10. DRILLER'S CERTIFICATION This well was drilled under my supervision and the report is true to the
7. TEST METHOD	WELL TES D: Bailer		===== A Pump 	x Ai	==== r Lift	best of my knowledge. Name

NV Contractors No.

Date 2-13 -03

Signed

NV Driller's Lic (on site) 2121

14170

By driller performing actual drilling on site or contractor

48-Hour Drawdown Test (Feb. 24~26, 2003) Falcon Capital Domestic Well

Γ		Time	Time	Total Combined	Depth to	Totalizer		Flow	Remarks
	- 1		interval	Time	Water	Reading	S	Rate	or ·
L	Step		(Minutes)	(Minutes)	(Ft.)	(Gal.)	(Ft.)	(GPM.)	Notes
	_ 1	10:10:40	0.0		246.83	26	0		Q=200gpm
	1		1.0	1.0	275.00		28.17		2/24/2003
	1		1.0	2.0	278.92		32.08	200	2/24/2003
	1		1.0	3.0	281.92		35.08	200	2/24/2003
	1		1.0	4.0	284.08		37.25	200	2/24/2003
L	1		1.0	5.0	285.08	·	38.25	200	2/24/2003
	1		1.0	6.0	286.00		39.17	200	2/24/2003
	1		2.0	8.0	287.67		40.83	200	2/24/2003
L	_1		2.0	10.0	287.92	46	41.08	200	2/24/2003
L	_1_	· · · · · · · · · · · · · · · · · · ·	10.0	20.0	288.58		41.75	200	2/24/2003
. [1		10.0	30.0	288.83		42.00	200	2/24/2003
L	1		10.0	40.0	289.08		42.25	200	2/24/2003
` 	1		10.0	50.0	289.25		42.42	200	2/24/2003
L	1	11:10:40	10.0	60.0	289.29		42.46	200	2/24/2003
Ļ	1	11:30:40	20.0	80.0	289.75		42.92	200	2/24/2003
L	1	11:50:40	20.0	100.0	290.00		43.17	200	2/24/2003
L	1	12:10:40	20.0	120.0	290.00		43.17	200	2/24/2003
	1	12:40:40	30.0	150.0	290.13		43.29	200	2/24/2003
Ļ	1	13:10:40	30.0	180.0	290.67		43.83	200	2/24/2003
Ļ	1	13:40:40	30.0	210.0	290.83		44.00	200	2/24/2003
L	1	14:10:40	30.0	240.0	290.79	486	43.96	. 200	2/24/2003
-	1	15:10:40	60.0	300.0	291.08		44.25	200	2/24/2003
Ļ	1	16:10:40	60.0	360.0	291.92	Not working	45.08	200	2/24/2003
ŀ	1	17:10:40	60.0	420.0	293.17	properly	46.33	200	2/24/2003
ŀ	1	18:10:40	60.0	480.0	293.00	for	46.17	200	2/24/2003
` -	1	19:10:40	60.0	540.0	292.00	the rest	45.17	200	2/24/2003
,	1	20:10:40	60.0	600.0	292.00		45.17	200	2/24/2003
-	1	21:10:40	60.0	660.0	292.00		45.17	200	2/24/2003
+	1	22:10:40	60.0	720.0	292.00		45.17	200	2/24/2003
. -	1	23:10:40	60.0	780.0 840.0	292.00 292.00		45.17	200	2/24/2003
-	1	0:10:40	60.0 60.0	900.0	292.00	·	45.17	200	2/25/2003 2/25/2003
-	1	1:10:40	60.0	960.0	292.54		45.17	200	2/25/2003
ŀ	1	2:10:40 3:10:40	60.0	1020.0	292.67		45.71		2/25/2003
-	1 1	4:10:40	60.0	1080.0	292.67		45.83 45.83	200 200	2/25/2003
1	1	5:10:40	60.0	1140.0	292.75		45.63	200	2/25/2003
H	1	6:10:40	60.0	1200.0	292.67		45.83	200	2/25/2003
·	1	7:10:40	60.0	1260.0	292.67		45.83	200	2/25/2003
ŀ	1	8:10:40	60.0	1320.0	292.75		45.92	200	2/25/2003
-	1	9:10:40	60.0	1380.0	292.83		46.00	200	2/25/2003
1	2	10:10:40	60.0	1440.0	292.92		46.08	250	Q=250 gmp
	2	11:10:40	60.0	1500.0	314.92		68.08	250	2/25/2003
` -	2	12:10:40	60.0	1560.0	314.33	<u> </u>	67.50	250	2/25/2003
۱ŀ	2	13:10:40	60.0	1620.0	312.33		65.50	250	2/25/2003
[2	14:10:40	60.0	1680.0	313.67		66.83	250	2/25/2003
'	2	15:10:40	60.0	1740.0	313.83		67.00	250	2/25/2003
ŀ	2	16:10:40	60.0	1800.0	313.92		67.08	250	2/25/2003
L		10.10.40	00.0	1000.0	010.02	L	07.00	200	

2	17:10:40	60.0	1860.0	314.00	67.17	250	2/25/2003
2	18:10:40	60.0	1920.0	314.00	67.17	250	2/25/2003
2	19:10:40	60.0	1980.0	314.00	67.17	250	2/25/2003
2	20:10:40	60.0	2040.0	314.00	67.17	250	2/25/2003
2	21:10:40	60.0	2100.0	314.00	67.17	250	2/25/2003
2	22:10:40	60.0	2160.0	314.00	67.17	250	2/25/2003
2	23:10:40	60.0	2220.0	314.00	67.17	250	2/25/2003
~ 2	0:10:40	60.0	2280.0	314.00	67.17	250	2/26/2003
2	1:10:40	60.0	2340.0	314.00	67.17	250	2/26/2003
2	2:10:40	60.0	2400.0	314.00	67.17	250	2/26/2003
2	3:10:40	60.0	2460.0	314.00	67.17	250	2/26/2003
2	4:10:40	60.0	2520.0	314.00	67.17	250	2/26/2003
2	5:10:40	60.0	2580.0	314.00	67.17	250	2/26/2003
2	6:10:40	60.0	2640.0	314.54	67.71	250	2/26/2003
2	7:10:40	60.0	2700.0	314.54	67.71	250	2/26/2003
2	8:10:40	60.0	2760.0	314.54	67.71	250	2/26/2003
2	9:10:40	60.0	2820.0	314.54	67.71	250	2/26/2003
2	10:10:40	60.0	2880.0	313.50	66.67	250	2/26/2003

Aquifer Parameter Estimation (Jacob's Method)

ds=

√ 5.63 ft

Q≃

200 gpm

0.4456 cfs

t0=

0.000012 min

2.3/(4*3.14159)=

0.183028339

T=

0.014 sqft/s

1251.6 sqft/day

r

0.33 ft

s

0.00021

Step Drawdown Calculation


Q		
gpm	s/Q=Y	s (ft)
200	0.230833333	46.17
250	0.270826667	67.71

Y=0.0007999xQ+0.07086


	cfs	gpm		Drawdown (ft)	Depth (ft)
Γ	1	448.88	0.429919112	193.0	439.8
Ē	1.2	538.656	0.501730934	270.3	517.1
Г	1.5	673.32	0.609448668	410.4	657.2

0.8911068	400	0.39082	156.3	403.2
1.1138834	500	0.47081	235.4	482.2
1.3366601	600	0.5508	330.5	577.3


48-HR DRAWDOWN TEST DATA (Feb. 24~26, 2003) Falcon Capital Domestic Well



48-HR DRAWDOWN TEST DATA (Feb 24, 2003) Falcon Capital Domestic Well



Step-Drawdown Test (February 24 & 26, 2003) Falcon Capital Domestic Well



Recovery Following 48-Hour Drawdown Test (Feb. 24~27, 2003) Falcon Capital Domestic Well

	Time	Time	Time Since	Total Combined	Ţime	Depth to	Drawdown	Remarks
		interval	Pumping Stopped	Time	Ratio	Water	S	or
Step		(Minutes)	(Minutes)	(Minutes)		(Ft.)	(Ft.)	Notes
Recov.	10:10:40	·	0.0	2880.0		313.5	66.67-	2/26/2003
Recov.		1.0	1.0	2881.0	2881	247.67	0.84	
Recov.		1.0	2.0	2882.0	1441	247.67	0.84	
Recov.		1.0	3.0	2883.0	961	247.67	0.84	
Recov.		1.0	4.0	2884.0	721	247.67	0.84	
Recov.		1.0	5.0	2885.0	577	247.67	0.84	
Recov.		1.0	6.0	2886.0	481	247.67	0.84	
Recov.		2.0	8.0	2888.0	361	247.67	0.84	
Recov.		2.0	10.0	2890.0	289	247.67	0.84	
Recov.		10.0	20.0	2900.0	145	247.79	0.96	
Recov.		10.0	30.0	2910.0	97	247.79	0.96	
Recov.		10.0	40.0	2920.0	73	247.75	0.92	
Recov.		10.0	50.0	2930.0	59	247.73	0.90	
Recov.		10.0	60.0	2940.0	49	247.73	0.90	
Recov.	• •	20.0	80.0	2960.0	37	247.71	0.88	
Recov.		20.0	100.0	2980.0	30	247.67	0.84	
Recov.		20.0	120.0	3000.0	25	247.66	0.83	
Recov.		30.0	150.0	3030.0	20	247.66	0.83	
Recov.		30.0	180.0	3060.0	17	247.58	0.75	
Recov.		30.0	210.0 🤲	3090.0	15	247.54	0.71	. >.
Recov.		30.0	240.0	3120.0	13	247.50	0.67	
Recov.		1200.0	1440.0	4320.0	3	247.40	0.57	

T=2.3*Q/(4*3.14159*DS)

DS=

0.3

Average Q=

225 gpm

0.501247549 cfs

43307.79 cf/day

T=

0.305808102 sqft/s

26421.82 sqft/day

2.3*Q/(4*3.1415926*T)=

0.3

S-stop=

66.67

2.25*T*t-stop=

118898.19


118898.19/S=

1.7113E+222

S=

2.7791E-217 (S is too small, discard)

RECOVERY FOLLOWING 48-HR DRAWDOWN TEST DATA (Feb. 24~27, 2003) Falcon Capital Domestic Well





DEP. D

			ON L M		IEK UF	IKAN	SIVILLIAL
00 Dar	monte Ranch P	arkway, Suite 1056	JAN 0 9 2007 WASHOE COUNTY OF WATER RESOUR	DATE	1/8/2007	JOB NUMBER	Serpa005
Reno, N	levada 89521		0 9 OE CO	Re: Ser	pa - Joy La	ke Road	Well
Ph: (77	5) 352-7800	Fx: (775) 352-7929	9 20 PRESC				
			VE 2007 PESOUP				
го:	Dan Drag	on, Wtr Resoul	rceManager				
	Washoe	County Water F	Resources				
	4930 Ene	ergy Way					
	Reno, NV	89502					
	WE ARE SEN	IDING YOU Att	ached	Under Sep	arate cover via _		the following items:
	☐ Shop Dra	wings	nts	Plans			☐ Specifications
	□ Copy of L	etter	ange Order				
	Т						
OPIES		E 1 (0	II - 66 1 - 1 - 1 - 1	DESCRIPTIO		***************************************	
1	2/5/2003	The second secon	ll off Joy Lake F				
1_	3/25/2003	Water Quality I	Results for well	off Joy Lake	Road - Joh	in Serpa	
	L						
THESE		SMITTED as checked			Overnight		d Delivered
	For approv		proved as submitted		cop		
	For your u		proved as noted		copie		tion
	As reques		turned for corrections	☐ Return	for cor	rected prints	
	☐ For review	w and comment	Ш				_
							forwarding copies
			aken from the well	in 2003. These	e are for your	review. Ple	ease call me if you
nave a	ny questions			·			
					Received by		And the second s
					Agency		
					Date		
Copy 1	to: File				()	m > 15	
				Sign	ed Gregory	M. Bilye	J
				_ /	/ /	-	

Nevada State Health Laboratory

1660 N. Virginia 5t. Reno, Nevada 89503-1783

FAX: (775) 688-1460

(775) 688-1335

Lab ID: 158772 Sample Type: SDWA

Sampled: 2/24/03 Received: 2/24/03

SAMPLE INFORMATION

Township: 17N Range: 19E Section: 23

General Location: APN 46 080 38

Source Address: JOY LAKE RD-WASHOE VALLEY

REPORT TO

Name: GREGORY M BILYEU

Company:

Address: 500 DAMONTE RANCH PARKWAY #10

City: RENO

State: NV Zip: 89521

Name: FALCON CAPITAL LLC

Address: PO BOX 456 City: ZEPHYR COVE

State: NV Zip: 89448

The results below are representative only of the sample submitted to this laboratory.

	Result	Reporting	Results	Reporting
ROUTINE DOMESTIC			in ppm	Limit
TDS @	: TII DAM	Limit	TRACE METALS:	
	100	• •	Cadmium:	0.001
180 Deg. C:	188	10	Chromium:	0.001
Hardness:	99	N/A	Lead:	0.001
Calcium:	23	5	Mercury:	0.0005
Magnesium:	10	5 5 5 5 5 5	Selenium:	0.001
Sodium:	. 22	5	Silver:	0.001
Potaseium:	3	5	Antimony:	C.001
Sulfate:	7	5	Beryllium:	0.001
Chloride:	1		Nickel:	0.001
Nitrate as N*:	0.1	0.1	Thallium:	C.0005
Alkalinity:	142	10	• •	•
Bicarbonate:	173	N/A	OTHER:	
Carbonate:	0	N/A	MBAS:	¢.1
Fluoride:	0.12	0.1	Nitrite-N:	0.01
	< 0.003	0.003	Cyanide:	0.005
Iron:	0.32	0.05	BOD:	2
Mangarese:	0.01	0.02	COD:	10
Copper;	0.00	0.02	Kjeldahl-N:	0.1
Zinc:	0.01	0.05	Ortho-P:	0.01
Barium:	0.05	0.02	Total-P:	0.01
Boron:	0.0	0.1	Aluminum:	0.02
Silica:	59	1	Ammonia:	0.1
Color:	3 SU	3 SU	-	V.2
Turbicity:	3.9 NTU	0.4 NTU	RADIOCHEMISTRY: pCi/l	pCi/l
pH:	8.27 SU	N/A	Gross Alpha:	3
EC:	300 SU	15 SU	Gross Beta:	3
SI @ 20 deg. C;	0.26	N/A	Uranium:	.
temp at time of		_deg. C		
•	· -			

ppm = parts per million, milligrams per liter S.U. = Standard Units *Nitrate is reported as Nitrate + Nitrite as N Remarks: Trace metal reporting limits (excluding mercury) reflect undiluted sample, multiply reporting limit by ____ for this sample.

SR. 3/21103

RESULTS REPORTED


MAR 2 5 2003

Dewey Data

WASHOE CITY

COMPANY : MCKAY DRILLING **OTHER SERVICES:** WELL **WASHOE CITY** 500-D **WASHOE CITY** LOCATION/FIELD INVOICE COUNTY : WASHOE 1674 STATE : NV. RANGE: N/A SECTION : N/A **TOWNSHIP** : N/A DATE : 02/05/03 PERMANENT DATUM: N/A DEPTH DRILLER 700 FT. KB. : N/A : N/A LOG BOTTOM 701.40 LOG MEASURED FROM: G/L DF LOG TOP DRL MEASURED FROM: G/L : N/A 3.90 GL **CASING DIAMETER: LOGGING UNIT CASING TYPE** : ACAMPO,CA. FIELD OFFICE **CASING THICKNESS:** RECORDED BY : SHANHOLTZER BIT SIZE : 10 **BOREHOLE FLUID** : CLAY/GE : ORIGINAL FILE MAGNETIC DECL. : 7 TYPE RM : 8.1 : 8044A MATRIX DENSITY : 2.71 RM TEMPERATURE : 76 **NEUTRON MATRIX** : Dolomite MATRIX DELTA T : 54 THRESH: 5000 WATER QUALITY-GOOD-400-600PPM TDS **MCKAY**

ALL SERVICES PROVIDED SUBJECT TO STANDARD TERMS AND CONDITIONS



· ·